



SUMITOMO PRODUCT SPECIFICATION

FutureFLEX®

TCxxMSOS DIELECTRIC HIGH PERFORMANCE OSP TUBE CABLE SERIES



SUMITOMO ELECTRIC LIGHTWAVE CORP.

78 TW Alexander Drive, Research Triangle Park, NC 27709

(919) 541-8100 or 1-800-358-7378

www.futureflex.com

SEL is a Member of the Sumitomo Electric Industries, Ltd. Group

Sumitomo Electric Lightwave reserves the right to improve or modify these specifications without notice.

CONTENTS

1.0	GENERAL	
1.1	Tube cable Description	3
1.2	Quality	3
1.3	Reliability	3
2.0	Tube Cable Design	
2.1	General	4
2.2	Construction	4
3.0	Tube Cable Characteristics	6
3.1	Performance	6
3.2	Tube and Jacket Markings	6
3.3	Reel Markings	6
3.4	Tube cable Ends	6
3.5	Standard Reel Lengths	6
3.6	Maximum Reel Lengths	7
4.0	Blowing Performance / Testing	7
5.0	Installation / Handling Practices	7
6.0	Ordering Information	7

1.0 GENERAL

This specification covers the design requirements and performance standards for FutureFLEX[®] Air-Blown Fiber[®] (ABF) dielectric, UV resistant low shrink outside plant tube cables. These tube cables are designed for outdoor tube cable infrastructures. The features described in this document are intended to provide information on the performance of Sumitomo Electric's FutureFLEX[®] tubes and aid in handling and use.

1.1 Tube Cable Description

Sumitomo's FutureFLEX[®] MSOS series tube cables are designed for use as an optical fiber cabling infrastructure in ABF applications that may or may not require non-conductive elements. The MSOS series tube cables are ideal for aerial or duct installations, or most Outside Plant environments. They may also be used in indoor applications where: 1) the tube cable is installed in rigid steel conduit or 2) no fire ratings apply. The tubes are made of a high performance black polyethylene and have a 6mm inside diameter and 8mm outside diameter. The tubes are wrapped with a non-conductive water-blocking tape. The outer jackets are made of a high performance black polyethylene with four extruded linear yellow stripes set at 90° apart. A ripcord is provided to aid in outer jacket removal. These tube cables are pulled or placed in routes for the purpose of individual tube connections to establish pathways for FutureFLEX[®] fiber bundle installation.

1.2 Quality

Sumitomo ensures a continuing high level of quality through ISO / TL9000 registered Quality Management Systems and our commitment to continuous improvement. Guaranteed, high quality products have been manufactured at Sumitomo's facility in Research Triangle Park, North Carolina since 1984.

1.3 Reliability

Sumitomo ensures product reliability through rigorous qualification testing of each product family to meet or exceed industry standards. Both initial and periodic qualification testing are performed to assure the tube cables' performance and durability in a field environment.

Sumitomo supports industry standards organizations such as Telcordia, Telecommunications Industry Association (TIA), International Telecommunications Union (ITU), International Electrotechnical Commission (IEC), American Society for Testing and Materials (ASTM), Rural Utilities Service (RUS), The Institute of Electrical and Electronics Engineers (IEEE), and Insulated Cable Engineers Association (ICEA).

2.0 TUBE CABLE DESIGN


2.1 General

Sumitomo's FutureFLEX® MSOS series tube cables provide a small diameter, lightweight, outdoor pathway for FutureFLEX® fiber bundle installations. FutureFLEX® ABF fiber bundles are available in Single Mode, 50 micron and 62.5 micron Multimode versions with 2, 4, 6, 12, 18, or 24 fiber strand counts. One fiber bundle can be field-installed in each tube.


2.2 Construction

SEL Part Number	Product Description	Outside Diameter (in.)	Max. Weight (lbs./kft.)	Max. Tensile Load (lbs.)
TC02MSOS	2-tubes, black, high performance, wrapped with water-blocking tape, ripcord, and black high performance outer jacket with 4 linear yellow stripes at 90° apart.	0.9	89	200
TC04MSOS	4-tubes, black, high performance, around a FRP central strength member, wrapped with water-blocking tape, ripcord, and black high performance outer polyethylene with 4 extruded yellow stripes at 90° apart.	0.9	141	200 with standard basket-weave grip or 500 with pulling eye
TC07MSOS	7-tubes, black, high performance, wrapped with water-blocking tape, ripcord, and black high performance outer jacket with 4 extruded yellow stripes at 90° apart.	1.1	196	400
TC19MSOS	19-tubes, black, high performance, wrapped with water-blocking tape, ripcord, and black high performance outer jacket with 4 extruded yellow stripes at 90° apart.	1.77	399	500


Drawings Are Not To Scale




2-Tube
Dielectric Low Shrink
OSP Cable
TC02MSOS



4-Tube
Dielectric Low Shrink
OSP Cable
TC04MSOS



7-Tube
Dielectric Low Shrink
OSP Cable
TC07MSOS



19-Tube
Dielectric Low Shrink
OSP Cable
TC19MSOS

3.0 TUBE CABLE CHARACTERISTIC

3.1 Performance

Property	Specification
Operation Temperature Range	-65° to +158°F
Minimum Bend Radius (During / After Installation)	20 / 10 x tube cable outside diameter

3.2 Tube and Jacket Markings

The outside surface of each tube is marked every two (2) inches with the tube designation number. (1 through 19)

The outside surface of each jacketed cable is marked every two (2) feet with the following information:

'Phone Receiver' SEL FutureFLEX® (SEL Part No.) (#)-Tube Dielectric OSP Optical Fiber Cable, A-(Lot #-1, -2, -3, etc.) (Seq. Ftg.) 1-877-356-FLEX WWW.FUTUREFLEX.COM →

3.3 Reel Markings

The outside of each flange is marked with the Sumitomo Electric Lightwave Corp. product part number, the tube cable manufactured length in feet, and the text "Do Not Lay Flat."

3.4 Tube Cable Ends

Both ends of the tube cable are accessible on the reel. Each tube is sealed with a plastic cap or plug. Tube cable ends are sealed with a heat shrink end cap.

3.5 Standard Reel Lengths

Sumitomo Part No.	Std Reel Length (ft)	Std Reel H x W (in)	Minimum Drum Diameter (in)	Std Reel Weight (lbs) Empty	Std Reel Weight (lbs) Full
TC02MSOS	1000	36 x 17	18	55	144
TC04MSOS	1000	54 x 20	40	116	257
TC07MSOS	1000	54 x 36	40	137	333
TC19MSOS	1000	64 x 49	40	420	819

Notes:

- Standard Reel Length tolerances are $\pm 5\%$
- All Reel Widths shown are approximate values only and measured across outside-of-flanges
- If tube cable is re-spoiled, the Minimum Drum Diameter of the new reel shall be as shown to avoid damaging tube cable product
- All Empty and Full Reel Weights shown are approximate values only

3.6 Maximum Reel Lengths

Sumitomo Part No.	Max Reel Length (ft)	Max Reel H x W (in)	Minimum Drum Diameter (in)	Max Reel Weight (lbs) Empty	Max Reel Weight (lbs) Full
TC02MSOS	3000	60 x 49	40	420	686
TC04MSOS	3000	60 x 49	40	420	842
TC07MSOS	3000	60 x 49	40	420	1008
TC19MSOS	2500	72 X 49	40	523	1521
TC19MSOS	3000	72 x 52	36	543	1740

Notes:

- Maximum Reel Length tolerances are $\pm 5\%$
- All Reel Widths shown are approximate values only and measured across outside-of-flanges
- If tube cable is re-spoiled, the Minimum Drum Diameter of the new reel shall be as shown to avoid damaging tube cable product
- All Empty and Full Reel Weights shown are approximate values only

4.0 Blowing Performance / Testing

Each finished tube cable on its reel is required to pass a 5mm diameter steel ball from end to end using 70 psi (+/-10 psi) gas pressure.

5.0 Installation / Handling Practices

Sumitomo has incorporated a wide range of technical support and training services for our tube cable products into our Technical Support Services (TSS) program. TSS offers training in the areas of cable installation, sheath entry, splicing, testing, and system troubleshooting. The services are available in a variety of media formats and can be customized to better accommodate individual training needs. The TSS program consists of an extensive series of recommended procedure documents, training courses with classroom and hands-on instruction. Please contact Sumitomo's Customer Service department for more information.

6.0 Ordering Information

To learn more about Sumitomo's cables or to place an order, call, fax, e-mail, or write us at:

Sumitomo Electric Lightwave Corp
78 Alexander Drive
Research Triangle Park, NC 27709
Attn: Customer Service Department

Phone: 800-358-7378
919-541-8100
Fax: 919-541-8265
E-mail: info@sumitomoelectric.com

Sumitomo Electric Lightwave reserves the right to improve, enhance, or modify the cable's features and specifications. For special requirements different than those shown above, please contact our Inside Sales Department. Each Sumitomo Electric Lightwave Corp. optic cable and/or its manufacture may be covered by one or more of the following US Patents: 4,715,677 4,729,629 4,763,983 4,770,489 4,828,349 4,953,945 5,043,037 5,082,347 5,165,003 D331,567